

ACRYLIC RESURFACER 367-43

Pure Acrylic Based Resurfacer

ACRYLIC RESURFACER 367-43

Pure Acrylic Based Resurfacer

Product Features:

- 100% pure acrylic-based filler/leveling material with a mixture of silica sand and water.
- Fills gaps in concrete or asphalt substructures and hides aggregate profiles.
- Smoothens concrete or asphalt substructures.

Advantages:

- Hard and highly wear-resistant.
- Easy mixing on the field.
- Dries quickly.
- Cost-effective.
- Easy application.
- High adhesion.
- Ready-to-use product.

Color: Black

Product Properties (at 20°C)

Specific Gravity (approx)	: 1.55 g/cm ³
Solid Content (% by weight)	: 68%
Touch Dry Time	: 20 minutes
Time Between Coats	: 2 hours
Theoretical Consumption	: 0.600 kg/m ² (for one coat)

Surface Preparation:

Surfaces should be cleaned from oil, dirt, mortar residues, dust, and other contaminants.

Application Process:

ACRYLIC RESURFACER 367-43 contains suitably selected silica texture in its formulation. If necessary, up to 5% tap water* can be added before application. Mix thoroughly with a slow-speed mixer until a homogeneous mixture is obtained.

*The amount of water may vary depending on ambient temperature. In hot weather, up to 5% more water can be added.

Consumption:

Theoretical consumption: 0.600 kg/m² (depending on surface permeability and porosity), applied on floors with its special application tool, a rubber squeegee.

Do not apply if the temperature is below 14°C or above 35°C.

ACRYLIC RESURFACER 367-43

Pure Acrylic Based Resurfacer

Ref. No: UTD-1590
Issue Date:01.01.2004
Revision Date:12.03.2024
Page:1/2

Important Note:

Consumption may vary depending on surface roughness, ambient temperature, and application technique. The values provided here are values found under laboratory conditions on concrete/wear asphalt at recommended mixing ratios.

Packaging:

20 kg plastic bucket or 60 kg plastic barrels.

Storage Conditions:

The product should be stored between 15°C and 35°C, in closed and dry storage areas in its unopened original packaging. Shelf life (warranty) is 12 months from the date of manufacture when stored in a cool, dry place. Do not expose the products to sunlight outdoors. Protect from freezing in cold weather.

Safety and Relevant Data:

ACRYLIC RESURFACER 367-43 is not hazardous and does not contain formaldehyde, asbestos, mercury, lead, or chromate and their derivatives. The product contains fire retardant additives. For detailed information on safe handling, occupational health, and safety, please refer to the relevant Material Safety Data Sheet (MSDS).

NOTE

The explanations provided in this technical data sheet are based on test evaluations and results conducted according to relevant standards, intended to guide applicators. As workmanship, weather conditions, construction, equipment used, and other variables that may affect results are entirely beyond our control, UNICA does not provide any explicit or implicit warranty regarding this material. UNICA only guarantees that the material conforms to its product specifications, and its sole responsibility towards the buyer or user of this product is limited to the replacement value of the product in case of manufacturing defects. Under no circumstances shall UNICA be liable for any direct or incidental, special, or consequential injury, loss, or damage arising from the material or its application. UNICA shall not be held responsible in any way for any defects, alterations, or changes in conditions in the substrate where its products are applied.